


Fuel specification.

See chapter **Other product information** for more information.

3.0GS	93 Octane (RON) unleaded fuel**
4.3GL, 4.3GS	93 Octane (RON) unleaded fuel**
4.3Gi	93* Octane (RON) unleaded fuel**
5.0GL	93 Octane (RON) unleaded fuel**
5.0Gi	93* Octane (RON) unleaded fuel**
5.7GS	93 Octane (RON) unleaded fuel**
5.7GSi	93* Octane (RON) unleaded fuel**

* If 93 octane (RON) is not available, gasoline down to 90 octane (RON) can be used.

** Leaded gasoline can be used if unleaded is unavailable.

 **WARNING!** Fuel is extremely flammable and highly explosive under certain conditions. Always stop the engine and do not smoke or allow open flames or sparks near the boat when refuelling.

When filling the fuel tanks, ground the tanks to the source of fuel by holding the hose nozzle firmly against the side of the deck filler plate or ground it in some other manner. This action prevents static electricity build-up which could cause sparks and ignite fuel vapours.

Fuel leakage can contribute to a fire and/or explosion.

SX drive

Designation	SX-C, SX-M
Oil grade/viscosity	VP 1141572-6 (API GL5 SAE75/90) Synthetic
Oil capacity	2.1 liters
Ratio	1.43:1, 1.51:1, 1.60:1, 1.66:1, 1.79:1, 1.89:1, 1.97:1, 2.18:1

Power Trim hydraulic system

Oil grade	ATF (Dexron II)
Oil capacity	1.6 liters

Power Steering

Oil grade	ATF (Dexron II)
-----------------	-----------------

DP-S drive

Designation	DP-S, DP-SM
Oil grade/viscosity	VP 1141572-6 (API GL5 SAE75/90) Synthetic
Oil capacity	2.4 liters
Ratio	1.78:1, 1.95:1, 2.32:1

Power Trim hydraulic system

Oil grade	ATF (Dexron II)
Oil capacity	1.6 liters

Power Steering

Oil grade	ATF (Dexron II)
-----------------	-----------------